

Vue d'ensemble

- M12, male, A-coded; 4-poles; TPE-S, 200 cm; M12, female, A-coded; 4-poles
- Dragchain capable; suitable for robotics $\pm 180^\circ/m$; suitable for food & beverage
- Head A: IP65, IP68, IP69K; Head B: IP65, IP68, IP69K
- ECOLAB tested
- Halogen free



Caractéristiques techniques

Side A		Cable	
Head A: Connection	M12	Cable: Temperature range (fixed)	- 40 ...+ 105 °C
Head A: Angle cable outlet	0°	Operating voltage (only UL listed)	30 V AC/DC
Head A: Gender	Male	Shielded	No
Head A: Coding	A	Bending radius (fixed)	23,5 mm
Head A: No. of poles	4	Number of wires	4
Head A: LED	No	Number and diameter of wires	4x0,34
Head A: Width across flats	AF14	Cable length	200 cm
Head A: Tightening torque	0,6 Nm	Acceleration (C-track)	max. 10 m/s ²
Head A: Knurled nut material	Stainless steel (V4A)	AWG	22
Head A: Body color	Blue	Bending radius (fixed)	min. 5 × outer diameter
Labeling sleeve side A	No	Torsion speed	max. 35 cycles/min
Side B		Bending radius (mobile)	min. 10 × outer diameter
Head B: Connection	M12	Cable weight	approx. 29,7 g/m
Head B: Angle cable outlet	90°	Conductor structure	42 × 0,1 mm
Head B: Gender	Female	Cable diameter	4,7 mm ± 5%
Head B: Coding	A	Conductor: Material	Copper, bare
Head B: No. of poles	4	External sheath: Material	TPE-S
Head B: LED	No	Insulation: Material	PP
Head B: Width across flats	AF14	No. of bending cycles (C-track)	approx. 400000 Cycles
Head B: Tightening torque	0,6 Nm	Nominal voltage	300 V AC
Head B: Knurled nut material	Stainless steel (V4A)	No. of torsion cycles	approx. 200000 Cycles
Head B: Body color	Blue	Paired stranding	No
Head B: Gasket material	EPDM	Single wire diameter	0,1 mm
Labeling sleeve side B	No	Cable: Test voltage	3 kV
Cables		Torsion stress in °	± 180 °/m
Cable length	200 cm	Total stranding	4 wires strand
Shielded	No	Travel speed (C-track)	max. 3 m/s
Conductor structure	42 × 0,1 mm	Traversing path (horizontal)	max. 10 m
AWG	22	Wire cross section	0,34 mm ²
External sheath: Material	TPE-S	Wire processing	No
External sheath: Color	Blue	Wire diameter incl. isolation	1,27 mm ± 5%
Cable diameter	4,7 mm ± 5%	External sheath: Color	Blue
Wire cross section	0,34 mm ²	Données électriques	
Cable		Operating voltage (only UL listed)	30 V AC/DC
Cable: Temperature range (mobile)	- 25 ...+ 105 °C		

Caractéristiques techniques

Données électriques

Nominal voltage	300 V AC
Contact resistance	max. 30 mOhm
Operating current per contact	max. 4 A

Données mécaniques

Head A: Degree of protection	IP65, IP68, IP69K
Head B: Degree of protection	IP65, IP68, IP69K
Bending radius (mobile)	min. 10 × outer diameter
Bending radius (fixed)	min. 5 × outer diameter
No. of bending cycles (C-track)	approx. 4000000 Cycles
Torsion speed	max. 35 cycles/min
Torsion stress in °	± 180 °/m
No. of torsion cycles	approx. 2000000 Cycles
Acceleration (C-track)	max. 10 m/s ²
Travel speed (C-track)	max. 3 m/s

Conditions ambiantes

Cable: Temperature range (fixed)	- 40 ...+ 105 °C
Dragchain capable	Oui
Head A: Chemical resistance	Chemical resistance tested according to ECOLAB. If other media are used, the material resistance must be tested according to the application.
Head A: Flame resistance	HB (UL 94)
Head A: Oil resistance	Good resistance to ASTM 1 oil and mineral oils. Limited resistance to hydraulic oils. If other oils are used, the resistance must be checked in relation to the application.

Conditions ambiantes


Head A: Acid and alkali resistant	Chemical resistance tested according to ECOLAB. If other media are used, the material resistance must be tested according to the application.
Head A: Pollution degree	3
Head B: Chemical resistance	Chemical resistance tested according to ECOLAB. If other media are used, the material resistance must be tested according to the application.
Head B: Flame resistance	HB (UL 94)
Head B: Oil resistance	Good resistance to ASTM 1 oil and mineral oils. Limited resistance to hydraulic oils. If other oils are used, the resistance must be checked in relation to the application.
Head B: Acid and alkali resistant	Chemical resistance tested according to ECOLAB. If other media are used, the material resistance must be tested according to the application.
Head B: Pollution degree	3
Cable: Acid and alkali resistant	Good (analogue FDA 21 178.3620, 178.3297, 177.1520)
Cable: Silicone-free	Oui

Commercial data

Eclass	27060311
--------	----------

Side A

Coding



Side B

Coding




Schéma de raccordement

