

Vue d'ensemble

- M8, female, A-coded; 4-poles; PUR, 100 cm, shielded, free cable end
- Dragchain capable
- Head A: IP65, IP67
- Cable: good resistance against chemicals, flames, oils
- Halogen free



Caractéristiques techniques

Side A		Cable	
Head A: Connection	M8	Length tolerance	+ 5 cm
Head A: Angle cable outlet	0°	Cable length	100 cm
Head A: Gender	Female	Acceleration (C-track)	max. 25 m/s ²
Head A: Coding	A	AWG	26
Head A: No. of poles	4	Bending radius (fixed)	min. 5 × outer diameter
Head A: LED	No	Bending radius (mobile)	min. 10 × outer diameter
Head A: Width across flats	AF9	Cable weight	approx. 23,1 g/m
Head A: Tightening torque	0,4 Nm	Conductor structure	18 × 0,1 mm
Head A: Knurled nut material	Zinc-pressure die casting, surface Ni	Cable diameter	4,6 mm ± 5%
Head A: Body color	Black	Conductor: Material	Copper, bare
Head A: Gasket material	FKM	External sheath: Material	PUR
Labeling sleeve side A	Yes	Insulation: Material	TPE
Side B		Shielding: Material	Copper, tinned
Head B: Connection	Open-ended wires	No. of bending cycles (C-track)	approx. 5000000 Cycles
Labeling sleeve side B	Yes	Nominal voltage	300 V
Cables		Paired stranding	No
Cable length	100 cm	Single wire diameter	0,1 mm
Length tolerance	+ 5 cm	Cable: Test voltage	1,5 kV
Stripping length	20 mm	Total stranding	4 wires strand
Shielded	Oui	Travel speed (C-track)	max. 5 m/s
Conductor structure	18 × 0,1 mm	Traversing path (horizontal)	max. 5 m
AWG	26	Wire cross section	0,14 mm ²
External sheath: Material	PUR	Wire processing	No
External sheath: Color	Gray	Wire diameter incl. isolation	1 mm ± 5%
Cable diameter	4,6 mm ± 5%	External sheath: Color	Gray
Wire cross section	0,14 mm ²	Données électriques	
Cable		Operating voltage	max. 50 V AC / 60 V DC
Cable: Temperature range (mobile)	- 30 ...+ 80 °C	Operating voltage (only UL listed)	30 V AC/DC
Cable: Temperature range (fixed)	- 40 ...+ 80 °C	Nominal voltage	300 V
Operating voltage (only UL listed)	30 V AC/DC	Contact resistance	max. 30 mOhm
Shielded	Oui	Operating current per contact	max. 4 A
Shielding: Covering	approx. 85 %	Données mécaniques	
Bending radius (fixed)	23 mm	Head A: Degree of protection	IP65, IP67
Number of wires	4	Bending radius (mobile)	min. 10 × outer diameter
Number and diameter of wires	4x0,14	Bending radius (fixed)	min. 5 × outer diameter

Caractéristiques techniques

Données mécaniques

No. of bending cycles (C-track)	approx. 5000000 Cycles
Acceleration (C-track)	max. 25 m/s ²
Travel speed (C-track)	max. 5 m/s

Conditions ambiantes

Temperature range (mobile)	- 25 ...+ 80 °C
Temperature range (fixed)	- 25 ...+ 80 °C
Cable: Temperature range (fixed)	- 40 ...+ 80 °C
Dragchain capable	Oui
Head A: Chemical resistance	No
Head A: Flame resistance	HB (UL 94)

Conditions ambiantes


Head A: Oil resistance	ASTM 1 oil, mineral oils, limited to hydraulic oils
Head A: Acid and alkali resistant	No
Head A: Pollution degree	3
Cable: Chemical resistance	Good (DIN EN 60811-404)
Cable: Flame resistance	Conform UL 1581 §1090 (H), CSA FT2, IEC 60332-2-2
Cable: Oil resistance	Good (DIN EN 60811-404)
Cable: Silicone-free	Oui

Commercial data

Eclass	27060311
--------	----------


Side A

Technical drawing



Side B

Technical drawing



Coding





Schéma de raccordement



Dessin d'encombrement

