

# FCE 200DM300

Plastic fiber optic cable

Article number: 11708583

## Overview

- Diffuse type
- Sensing distance up to 235 mm
- Threaded sensing head M3, coaxial fiber layout for increased precision
- Plastic fiber 200 cm long, with bend protection
- Operating temperature up to +70 °C
- For compact fiber optic sensors FVDK 10 and OF10



Picture similar

## Technical data


### General data

|   |   |
|---|---|
| Particular characteristics              | Coaxial fiber layout<br>Bend protection |
| Operating principle                     | Diffuse type                            |
| Sensing distance Tw                     | 235 mm                                  |
| Fiber optic head                        | Cylindrical threaded                    |
| Operating temperature                   | -55 ... +70 °C                          |
| Exit angle                              | 60°                                     |
| Fiber optics can be shortened to length | Yes                                     |
| Integrated lens                         | No                                      |
| Adaptable lens                          | Yes                                     |
| Infrared light compatibility (1450 nm)  | No                                      |


### Mechanical data

|                              |                 |
|------------------------------|-----------------|
| Diameter Fiber               | 0.5 mm          |
| Width / diameter (head)      | 3 mm            |
| Height / length (head)       | 18.5 mm         |
| Material (head)              | Stainless steel |
| Thread                       | M3 x 0.5        |
| Bending radius (fixed)       | 15 mm           |
| Cable jacket diameter        | 1.25 mm         |
| Material cable jacket        | PE              |
| Material (fiber optic cable) | Plastic         |
| Length (fiber optic cable)   | 200 cm          |


## Dimension drawing



## Fiber arrangement



## Sensing distance diagram



# FCE 200DM300

Plastic fiber optic cable

Article number: 11708583

## Accessories

### Fitting fiber optic sensors

|          |                        |
|----------|------------------------|
| 11252204 | OF10.FR-GW2J.B2NV/A014 |
| 11244386 | OF10.FR-GW2J.B2CV/A014 |
| 11224111 | OF10.FR-PW1B.B2N       |
| 11224008 | OF10.FR-NW1B.B2CV      |
| 11224009 | OF10.FR-NW1B.B2N       |
| 11224110 | OF10.FR-PW1B.B2CV      |
| 11244384 | OF10.FR-GW2J.B2N/A014  |
| 10162867 | FVDK 10N5101           |
| 10162865 | FVDK 10N5101/S35A      |
| 10162866 | FVDK 10P5101           |
| 10162864 | FVDK 10P5101/S35A      |
| 11045446 | FVDK 10N66Y0           |
| 11045448 | FVDK 10N66Y0/S35A      |
| 11045460 | FVDK 10N66YR           |
| 11045445 | FVDK 10P66Y0           |
| 11045447 | FVDK 10P66Y0/S35A      |
| 11045449 | FVDK 10P66YR           |
| 11214490 | FVDK 10P66ZR           |
| 11214493 | FVDK 10P66Z0/S35A      |
| 11214478 | FVDK 10P66Z0           |
| 11214492 | FVDK 10N66ZR           |
| 11214494 | FVDK 10N66Z0/S35A      |
| 11214479 | FVDK 10N66Z0           |
| 11045462 | FVDK 10N66YM           |
| 11045464 | FVDK 10N66YS           |
| 11045461 | FVDK 10P66YM           |
| 11045463 | FVDK 10P66YS           |

### Mounting accessories

|          |                  |
|----------|------------------|
| 11708552 | ZTOOL-FBR.CUTTER |
|----------|------------------|

### Lenses and components

|          |                        |
|----------|------------------------|
| 11708559 | ZADAP-FBR.1_3MM        |
| 11708554 | ZLENS-FBR.M3_8MM_0.5MM |
| 11708555 | ZLENS-FBR.M3_8MM_2MM   |